

上海宏骏科技有限公司 Shanghai Hongjun Science & Technology Co., Ltd.



报告编号 Report No.: HJ-QAT-221153

第1页共4页

ASTM D6007-14 人造板小气候箱甲醛释放量检测 ASTM D6007-14 Standard Test Method for Determining Formaldehyde Concentrations in Air from Wood Products Using a Small-Scale Chamber CARB P2-TSCA Title VI

检测告

委 托 単 位	宿迁市久丰木制品厂					
Applicant _	Suqian Jiufeng Wood Products Co., Ltd.					
工厂编号 Mill No.	ICTT-17140					
样品类型 Sample Type _	单板芯的硬木胶合板 HWPW-VC					
检测类别 Test Purpose	定期检测 Quarterly Test					
签发日期 Report Date	2022-07-12					

Shanghai Hongjun Science & Technology Co., Ltd is California Air Resources Board (CARB) & EPA approved as a



上海宏骏科技有限公司 Shanghai Hongjun Science & Technology Co., Ltd.



报告编号 Report No.: HJ-QAT-221153

第2页共4页

注 意 事 项 Intentions

- 1. 报告无检测单位"检测专用章"无效; The testing report is invalid when there is no Chinese words stamp which means "Specfic Stamp for Testing Report".
- 2. 复印报告未重新加盖检测单位"检测专用章"无效,未经本公司书面授权,不得部分复制本报告; The copy of this testing report is invalid when is is no fresh Chinese words stamp. The testing report is not permitted to be full or partly copied without the written authorization of the inspection institution.
- 3. 若需以电话、传真或其它方式传送检测结果时,所发内容只作参考,以正式书面报告为准; If the testing result needs to be presented by telephone, fax or in any other way, the presenting message is only for reference. The results of the test are subject to the formal written report.
- 4. 报告涂改无效,无编制、审核、批准人签章无效;
 This testing report that is altered would be invalid and this testing report without the signatures of the one who prepares the report, the auditor and approver shall be invalid.
- 5. 本检测报告仅对来样负责; This testing report is responsible for the received samples only.
- 6. 对检测报告若有异议,应于收到报告之日起_5_日内向检测单位提出,逾期不予受理; If there is any objection to the testing report, it should be presented to the testing institution within 5 days from the date of receiving the test report. The objection shall not be accepted after the expiry of the prescribed time limit.

公司注册地址 Registration address: 上海市闵行区光华路 598 号 3 幢 1 楼 103-9

检测地址 Test address: 重庆市江北区港安二路 8 号 3 号楼 6F

邮政编码 Post code: <u>400025</u> 电 话 Tel: <u>023-63525678</u>

传 真 Fax: 023-63530958 E-mail: hjklab@163.com



上海宏骏科技有限公司 Shanghai Hongjun Science & Technology Co., Ltd.





报告编号 Report No.: HJ-QAT-221153

第3页共4页

报音编号 Report No	.: 11J-QA1-221133				<u> </u>		
		样品信息	Sample Informa	ition			
生产单位	宿迁市久丰木制品	7万					
MFG Name	Suqian Jiufeng Wo	ood Products Co., L	td.				
委托单位	宿迁市久丰木制品						
Applicant	Suqian Jiufeng Wo	ood Products Co., L	td.				
样品类型	HWPW-VC			树种类型 Wood Material	杨树 Poplar		
Sample Type	表面处理 Surface Coated: 是 Yes□ 否 No 🗹			单面 Single□ 双面 Double-side□			
样品规格及数量 Sample Quantity& Size	150*250mm 3Sets (3 PCS / Set)			样品厚度 Sample Thickness	10mm-9plies		
生产日期 Production Date	2022-05-30	采样日期 Sample Date	2022-06-13	收样日期 Sample Received	2022-06-19		
产品/批次号	20220530	20220520 样品描述		Sampled by SHST representative in accordance			
Product/Batch ID	20220330	Sample l	Description	with ATCM regulation and sampling procedure			
样品包装状态 Sample	Packaging Status:	密封完好 Packag	ing well while recei	ived.			
检测项目	田磁軽故豊(小々	三候筠注)Formale	lahyda Emission (S	Small Scale Chamber)			
Test Item	甲醛释放量(小气候箱法)Formaldehyde Emission(Small-Scale Chamber)						
检测依据	ASTM D6007-14: Standard Test Method for Determining Formaldehyde Concentrations in Air from Wood						
Test Standard	Products Using a Small-Scale Chamber						
判定依据	美国联邦法案 40 CFR Part 770(EPA TSCA Title VI)第§770.10 及加州空气资源局 93120 法规						
Conformity Standard							
检测日期	2022-07-04			报告日期	2022-07-12		
Test Date	77 TV 47 TX 12 Y2 TV 16			Report Date			
		则 The samples had 引(小与候籍注):		-14 标准进行检测,检测	刚结 思		
检测结论							
Conclusion	AV ELIA DEL CALLED						
Conclusion							
	Testing unit (special seal for testing)						
				· •	變 👉		
	1.样品信息由委托单位提供。						
备注	Applicant to provi	de the information of	of the sample.		松洲土田土		
Note		样品平衡时间为?	•		世州专用草		
	According to the test standard, the sample conditioning costs 7 days.						



上海宏骏科技有限公司





Shanghai Hongjun Science & Technology Co., Ltd.

报告编号 Report No.: HJ-QAT-221153

第4页共4页

检测信息 Test Data

样品在检测前封边放置在温度为 24±3℃(75±5°F)和相对湿度为 50±5%的箱体内调节,样品调节的箱体甲醛背景浓度低于 0.10ppm.

The samples were covered the edges with aluminum tape and stored in a room maintained at $50\pm5\%$ RH, $24\pm3\%$ (75 $\pm5\%$ F) prior to testing . The formaldehyde background concentration in the air where the specimens were conditioned was documented at <0.10 ppm.

然后将样品放入甲醛背景浓度低于 0.02ppm 的气候箱(体积为 0.2 m³)中,气候箱维持 25±1℃湿度 50±4%,进气的甲醛浓度低于 0.02ppm 至少 3 次完全空气置换后,以每分钟 1 升的速度采箱体内空气 30 分钟,以分光光度计 7230G 进行分析。甲醛释放量值修正到相对湿度 50%,温度 77°F 的标准值。

Then put the sample into the chamber (volume = 0.2 m^3), and which was maintained at $25\pm1^{\circ}$ C and $50\pm4\%$. The formaldehyde concentration of make-up air and the chamber were both measured at <0.02 ppm. After allow time for no less than three full air changes, air samples were drawn at a rate of one (1) L/minute for 30 minutes. Emission values were determined with spectrophotometer analysis 7230G. The Formaldehyde Emissions are corrected to an emission level at standard conditions (50% RH and 77 °F).

221153-1 221153-2 221153-3	HX119 HX813 HX1#	2022-07-04 2022-07-04 2022-07-04	(m³/h) /m² 1.173 1.172 1.174	(mm) 10 10 10	(m ²) 0.225 0.225 0.225	(L/min) 4.40 4.40 4.40	(h) 2.83 2.83 2.83	(°C) 25.8 24.8 25.7	(%) 53.0 53.3 52.9	(ppm) 0.036 0.038 0.047
样品编号 Sample No.	箱编号 Small Chamber Test No.	检测日期 Test Date	箱 Q/A 值 Chamber Q/A Ratio	厚度 Thickness	暴露面积 Total Exposed Area	平均进 气流量 Flow	时间 Time	温度 Temp.	相对 湿度 RH	甲醛释放量 Formaldehyde Emission

ASTM D6007-14 检测结果满足美国联邦法案 40 CFR Part 770(EPA TSCA Title VI)第\$770.10 及加州空气资源局 93120 法规表格一中要求的单板芯的硬木胶合板第二阶段 0.05ppm 的限值要求。

The ASTM D6007-14 test results meet the §770.10 of 40 CFR Part 770 (EPA TSCA Title VI) & CARB 93120, Table 1, Phase 2 limitation of 0.05ppm for HWPW-VC.

附注 Note:

- 1. ASTM D6007-14 甲醛释放量检测在本实验室方法检出限(MDL)为 0.004ppm,低于 0.004ppm 视为未检出。The method detection limit in our laboratory for this method is 0.004ppm,Thus if the test result is less than 0.004ppm, it is regarded as not detect out HCHO.
- 2. 客户申请的测试判定规则为: IEC Guide 115:2007 第二程序—准确度法,不需要考虑不确定度。The applicable decision rules of this test are: IEC Guide 115:2007 Procedure 2 Accuracy method,do not subject to measurement uncertainty.

批准 Approved: た ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・	事核 Audit: 小戏名	编制 Prepared:
日期 Date: <u>2022-07-12</u>	_ 日期 Date: <u>2022-07-12</u>	日期 Date: <u>2022-07-12</u>
	报告结束 Report End	